



TECHNICAL DATA
URBAN 200 SPECIAL

CHASSIS

Frame	steel double cradle frame
Wheel base	1345 mm
Max length	2010 mm
Max width	800 mm
Max height	1110 mm
Seat height	830 mm
Ground clearance	300 mm
Footrest height	320 mm
Dry weight	110 kg
Fuel tank capacity	6,0 l.
Reserve	1,5 l.
Front suspension	Hydraulic fork with ø38 mm shaft
Rear suspension	Monoshock with adjustable spring preload
Shock absorber stroke	63 mm
Front wheel travel	170 mm
Rear wheel travel	185 mm
Front brake	wave brake disc ø245 mm
Rear brake	wave brake disc ø220 mm
Front rim	1,85 x 19
Rear rim	2,15 x 16
Front tyre	80/100 - 19 M/C
Rear tyre	120/90 - 16 M/C

ENGINE

Type	Single-cylinder, 4-stroke, air cooled, S.O.H.C.
Bore	66,0 mm
Stroke	58,2 mm
Displacement	199cc
Compression ratio	9,4:1
Carburettor	Mikuni BST 31 42AD
Feeding	Unleaded gasoline
Starter	Electric and mechanical starter
Lubrication	forced with pump
Ignition	Electronic
Spark plug	NGK DR8EA - DENSO X24ESR-U
Clutch	Wet multi-disc clutch
Primary trasmission	Z. 19/60
Gear box	5 speed
Secondary trasmission	Z 15/41
Engine oil	SAE 15W/50 (850cc)